

## Masters Prim Plus

**Code :** MPPLUS  
**Version :** 2  
**Date :** 13/07/2011

### BONDING AGENT FOR CLOSED SURFACES

#### FEATURES AND BENEFITS OF MASTERS PRIM PLUS

Promotes adherence on closed surfaces  
Regulates the surface porosity.  
Allows creating a barrier between the substrates and the decorative concrete  
Prevents the formation of bubbles in self levelling overlays  
Extends working time  
Can be use indoor and outdoor

This product is free VOC's – According to European Directive 2004/42/CE

#### DESCRIPTION

**Masters Prim Plus** is a synthetic resin in aqueous dispersion.  
It uses on all closed surfaces such as tiles, ceramic, paints, and waterproof surfaces (plasterboards, wood, etc...).  
It allows regularising the surface porosity promotes the adherence and extends the working time.

#### APPLICATION

##### PREPARING SURFACES

The surface must be clean, dry and free of dust and other substances such as paint, oil, grease, fluorescence, glue, or old sealers.

If you have any doubts about the cleanliness of the substrate, it is preferable to perform a light sanding with 120 grit.

##### APPLICATION

**Masters Prim Plus** must be applied with roller or brush in a single coat.  
Let it dry during 4 hours before applying your decorative concrete.

For porous surfaces, use **Masters Prim**.

#### TECHNICAL DATA

##### Presentation

**Form:** Single component  
**Packaging:** 1 or 5 liters  
**Coverage:** 1l for 10sqm  
**Colour:** Milky  
**Odour:** Without

##### Properties

**Type:** Synthetic resin and specific additives  
aqueous dispersion  
**VOCs:** Less than 1gr/l  
**Drying time to touch:** 4 hours  
**Drying time to sand:** 48 hours

#### PRECAUTION FOR USE AND STORAGE

This product is free VOC's. Use gloves, goggles and appropriate mask. Work in a ventilated area. Read the MSDS prior to use. The shelf life of this product is two years in original packaging and stored in a dry room away from frost and intense heat.

*All the data and recommendations in this sheet are the expression of our knowledge and of test results. They can not be considered as a warranty, involving our liability in case of misuse or the rules of the art have not been respected. Before using, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. The colours and effects in our colour charts are indicative, and cannot be considered as contractual. It is preferable to make a sample for each worker and each realisation.*