

FEATURES AND BENEFITS OF MASTERS ANTIQUE RELEASE

- Prevents stamping mats and skins to stick to the concrete
- Add a second colour to your achievement to create an antique effect.
- Creates a light cure effect due to its water repellent properties.
- Easier to apply compared to liquid release agent
- Existing in several colours
- Can be used either on a fresh concrete or on a stamping overlay
- Possibility to have a neutral colour

This product is free VOC's – According to European Directive 2004/42/CE

DESCRIPTION

Masters Antique Release is a colour release agent used for stamping concrete. Protect yourself by wearing a dust mask to prevent inhalation.

A

APPLICATION

The best tool to apply **Masters Antique Release** is a brush to glue wallpaper. Dip this dry brush into the bucket of powder release and fluff it to load the bristles. Then take the brush by the handle and use your wrist to flick the release on the surface in shaking vigorously near the ground. Apply a uniform layer on the entire surface.

When your colour release agent masks the colour of your colour hardener, that's enough. Don't apply too much release agent, especially with lighter textures.

Begin the stamping carefully. When you begin to remove your stamp, you can have a look under to see what you have done. The surface of the powder colour release helps determine if you have depressed the stamp completely. Regardless of the colour you are using, the release will lighten when it has been fully compacted by the stamp.

DATA

Presentation		Properties	
Form:	Single component ready to use	Type:	Talcum powder with additives and colour pigments
Packaging:	Bucket of 10kg	VOCs:	None
Coverage:	One bucket for 60sqm		
Colour:	See colour chart		

PRECAUTION FOR USE AND STORAGE

This product is free VOC's. Use gloves, goggles and appropriate mask. Work in a ventilated area. Read the MSDS prior to use. The shelf life of this product is two years in original packaging and stored in a dry room away from frost and intense heat.

All the data and recommendations in this sheet are the expression of our knowledge and of test results. They can not be considered as a warranty, involving our liability in case of misuse or the rules of the art have not been respected. Before using, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. The colours and effects in our colour charts are indicative, and cannot be considered as contractual. It is preferable to make a sample for each worker and each realisation.